


SCHEDA TECNICA TESSUTO (FABRIC SPECIFICATIONS)

NOME (NAME)	RECLUZ
--------------------	---------------

	METODO (METHOD)	VALORI (VALUE)
COMPOSIZIONE (COMPOSITION)	LEGGE (LAW) 883	70%VI 30%LI
ALTEZZA (WIDTH)	UNI EN 1773:1998	140 cm
PESO (WEIGHT)	UNI 5114:1982	394 g/m ²
MARTINDALE	UNI EN ISO 12947-2:2000	10.000 giri (turns)
PILLING TEST	UNI EN ISO 12945-2:2002 5000 CYCLES	--
SOLIDITA' ALLA LUCE (COLOURFASTNESS TO LIGHT)	UNI EN ISO 105-B02:2001	4/5
SOLIDITA' ALLO SFREGAMENTO (COLOURFASTNESS TO CROCKING) – SECCO (DRY)	UNI EN ISO 105-X12:2003	--
SOLIDITA' ALLO SFREGAMENTO (COLOURFASTNESS TO CROCKING) – UMIDO (WET)	UNI EN ISO 105-X12:2003	--

MANUTENZIONE (CLEANING)


L'articolo sopra descritto è conforme alle norme R.E.A.C.H. 1907/2006/CE
The item above described comply with the norms R.E.A.C.H. 1907/2006/CE

Compilato da QUA – Emiss. 20/02/09 Rev.0 - Sigla *OP*